

# Standard Fields

This section describes a set of standard message field definitions that should be used when similar concepts are needed. This will ensure the same concept has the same name and semantics across different APIs.

Name	Type
<code>name</code>	<code>string</code>
<code>parent</code>	<code>string</code>
<code>create_time</code>	<a href="https://github.com/google/protobuf/blob/master/src/google/protobuf/timestamp.proto">Timestamp</a> ( <a href="https://github.com/google/protobuf/blob/master/src/google/protobuf/timestamp.proto">https://github.com/google/protobuf/blob/master/src/google/protobuf/timestamp.proto</a> )
<code>update_time</code>	<a href="https://github.com/google/protobuf/blob/master/src/google/protobuf/timestamp.proto">Timestamp</a> ( <a href="https://github.com/google/protobuf/blob/master/src/google/protobuf/timestamp.proto">https://github.com/google/protobuf/blob/master/src/google/protobuf/timestamp.proto</a> )
<code>delete_time</code>	<a href="https://github.com/google/protobuf/blob/master/src/google/protobuf/timestamp.proto">Timestamp</a> ( <a href="https://github.com/google/protobuf/blob/master/src/google/protobuf/timestamp.proto">https://github.com/google/protobuf/blob/master/src/google/protobuf/timestamp.proto</a> )
<code>expire_time</code>	<a href="https://github.com/google/protobuf/blob/master/src/google/protobuf/timestamp.proto">Timestamp</a> ( <a href="https://github.com/google/protobuf/blob/master/src/google/protobuf/timestamp.proto">https://github.com/google/protobuf/blob/master/src/google/protobuf/timestamp.proto</a> )
<code>start_time</code>	<a href="https://github.com/google/protobuf/blob/master/src/google/protobuf/timestamp.proto">Timestamp</a> ( <a href="https://github.com/google/protobuf/blob/master/src/google/protobuf/timestamp.proto">https://github.com/google/protobuf/blob/master/src/google/protobuf/timestamp.proto</a> )
<code>end_time</code>	<a href="https://github.com/google/protobuf/blob/master/src/google/protobuf/timestamp.proto">Timestamp</a> ( <a href="https://github.com/google/protobuf/blob/master/src/google/protobuf/timestamp.proto">https://github.com/google/protobuf/blob/master/src/google/protobuf/timestamp.proto</a> )
<code>read_time</code>	<a href="https://github.com/google/protobuf/blob/master/src/google/protobuf/timestamp.proto">Timestamp</a> ( <a href="https://github.com/google/protobuf/blob/master/src/google/protobuf/timestamp.proto">https://github.com/google/protobuf/blob/master/src/google/protobuf/timestamp.proto</a> )
<code>time_zone</code>	<code>string</code>
<code>region_code</code>	<code>string</code>
<code>language_code</code>	<code>string</code>

Name	Type
<code>mime_type</code>	<code>string</code>
<code>display_name</code>	<code>string</code>
<code>title</code>	<code>string</code>
<code>description</code>	<code>string</code>
<code>filter</code>	<code>string</code>
<code>query</code>	<code>string</code>
<code>page_token</code>	<code>string</code>
<code>page_size</code>	<code>int32</code>
<code>total_size</code>	<code>int32</code>
<code>next_page_token</code>	<code>string</code>
<code>order_by</code>	<code>string</code>
<code>request_id</code>	<code>string</code>
<code>resume_token</code>	<code>string</code>
<code>labels</code>	<code>map&lt;string, string&gt;</code>
<code>deleted</code>	<code>bool</code>
<code>show_deleted</code>	<code>bool</code>
<code>update_mask</code>	<a href="https://github.com/google/protobuf/blob/master/src/google/protobuf/field_mask.proto">FieldMask</a> ( <a href="https://github.com/google/protobuf/blob/master/src/google/protobuf/field_mask.proto">https://github.com/google/protobuf/blob/master/src/google/protobuf/field_mask.proto</a> )

Name	Type
------	------

<code>validate_only</code>	<code>bool</code>
----------------------------	-------------------

## System Parameters

Besides the standard fields, Google APIs also support a set of common request parameters available across all API methods. These parameters are known as *system parameters*. For more information, see [System Parameters \(/apis/docs/system-parameters\)](/apis/docs/system-parameters).

[Previous](#)

[Next](#)



[Custom Methods \(/apis/design/custom\\_methods\)](/apis/design/custom_methods)

[Errors \(/apis/design/errors\)](/apis/design/errors)



Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 4.0 License \(https://creativecommons.org/licenses/by/4.0/\)](https://creativecommons.org/licenses/by/4.0/), and code samples are licensed under the [Apache 2.0 License \(https://www.apache.org/licenses/LICENSE-2.0\)](https://www.apache.org/licenses/LICENSE-2.0). For details, see the [Google Developers Site Policies \(https://developers.google.com/site-policies\)](https://developers.google.com/site-policies). Java is a registered trademark of Oracle and/or its affiliates.

Last updated 2020-06-22 UTC.