Lists operations that match the specified filter in the request. If the server doesn't support this method, it returns UNIMPLEMENTED.

NOTE: the name binding allows API services to override the binding to use different resource name schemes, such as users/*/operations. To override the binding, API services can add a binding such as "/v1/{name=users/*}/operations" to their service configuration. For backwards compatibility, the default name includes the operations collection id, however overriding users must ensure the name binding is the parent resource, without the operations collection id.

GET https://automl.googleapis.com/v1/{name}/operations

Parameters

name	string
	The name of the operation's parent resource.

Parameters

filter	string
	An expression for filtering the results of the request.
	• operation_id - for = or !=.
	 done - for = or !=. works0n - for = or !=.
	Some examples of using the filter are:
	• done=true> The operation has finished running.
	 worksOn = projects/my-project/locations/us- central1/datasets/5> The operation works on a dataset with ID 5.
	 worksOn = projects/my-project/locations/us- central1/models/15> The operation works on a model with ID 15.
pageSize	integer
	The standard list page size.
pageToken	string
	The standard list page token.
The request body mu	ust be empty.
If successful, the resi	ponse body contains an instance of <u>ListOperationsResponse</u>
	ce/rest/Shared.Types/ListOperationsResponse).

https://www.googleapis.com/auth/cloud-platform
F
For more information, see the <u>Authentication Overview</u>
(https://cloud.google.com/docs/authentication/).