

[Cloud Router](https://cloud.google.com/router/docs/) (<https://cloud.google.com/router/docs/>)

[Documentation](https://cloud.google.com/router/docs/) (<https://cloud.google.com/router/docs/>) [Guides](#)

Terminating BGP Sessions

For terminating BGP sessions, delete the associated resource, such as the Cloud VPN tunnel or VLAN attachment. After you delete the resource, the session is automatically terminated. You can terminate BGP sessions manually by using the `gcloud` command line tool. If you do, the tunnel or VLAN attachment remain, but Cloud Router doesn't advertise routes over them.

Run the `remove-bgp-peer` command, as shown in the following example:

```
gcloud compute routers remove-bgp-peer my-router --peer-name my-bgp-peer
```



Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 4.0 License](https://creativecommons.org/licenses/by/4.0/) (<https://creativecommons.org/licenses/by/4.0/>), and code samples are licensed under the [Apache 2.0 License](https://www.apache.org/licenses/LICENSE-2.0) (<https://www.apache.org/licenses/LICENSE-2.0>). For details, see our [Site Policies](https://developers.google.com/terms/site-policies) (<https://developers.google.com/terms/site-policies>). Java is a registered trademark of Oracle and/or its affiliates.

Last updated December 4, 2019.