Starts asynchronous cancellation on a long-running operation. The server makes a best effort to cancel the operation, but success is not guaranteed. If the server doesn't support this method, it returns `google.rpc.Code.UNIMPLEMENTED`. Clients can use `Operations.GetOperation` (/security-command-center/docs/reference/rest/v1beta1/organizations.operations/get#google.longrunning.Operations.GetOperation) or other methods to check whether the cancellation succeeded or whether the operation completed despite cancellation. On successful cancellation, the operation is not deleted; instead, it becomes an operation with an `Operation.error` (/security-command-center/docs/reference/rest/Shared.Types/ListOperationsResponse#Operation.FIELDS.error) value with a `google.rpc.Status.code` (/security-command-center/docs/reference/rest/Shared.Types/ListOperationsResponse#Status.FIELDS.code) of 1, corresponding to `Code.CANCELLED`.

POST
`https://securitycenter.googleapis.com/v1/{name=organizations/*/operations/*}:cancel`

The URL uses gRPC Transcoding (https://github.com/googleapis/googleapis/blob/master/google/api/http.proto) syntax.

Parameters

name	string
	The name of the operation resource to be cancelled.

The request body must be empty.

If successful, the response body will be empty.

Requires the following OAuth scope:

- `https://www.googleapis.com/auth/cloud-platform`

For more information, see the Authentication Overview
(https://cloud.google.com/docs/authentication/).