

Lists operations that match the specified filter in the request. If the server doesn't support this method, it returns **UNIMPLEMENTED**.

NOTE: the **name** binding allows API services to override the binding to use different resource name schemes, such as **users/\*/operations**. To override the binding, API services can add a binding such as **"/v1/{name=users/\*/operations}"** to their service configuration. For backwards compatibility, the default name includes the operations collection id, however overriding users must ensure the name binding is the parent resource, without the operations collection id.

**GET** `https://securitycenter.googleapis.com/v1/{name=organizations/*/operations}`

The URL uses [gRPC Transcoding](#)

(<https://github.com/googleapis/googleapis/blob/master/google/api/http.proto>) syntax.

#### Parameters

<b>name</b>	<b>string</b>
	The name of the operation's parent resource.

#### Parameters

<b>filter</b>	<b>string</b>
	The standard list filter.

## Parameters

<b>pageSize</b>	<b>number</b>
	The standard list page size.
<b>pageToken</b>	<b>string</b>
	The standard list page token.

The request body must be empty.

If successful, the response body contains an instance of [ListOperationsResponse](#) (</security-command-center/docs/reference/rest/Shared.Types/ListOperationsResponse>).

Requires the following OAuth scope:

- <https://www.googleapis.com/auth/cloud-platform>

For more information, see the [Authentication Overview](#) (<https://cloud.google.com/docs/authentication/>).