

Creates a finding. The corresponding source must exist for finding creation to succeed.

POST

`https://securitycenter.googleapis.com/v1/{parent=organizations/*/sources/*/}findings`

The URL uses [gRPC Transcoding](https://github.com/googleapis/googleapis/blob/master/google/api/http.proto)

(<https://github.com/googleapis/googleapis/blob/master/google/api/http.proto>) syntax.

Parameters

parent

string

Required. Resource name of the new finding's parent. Its format should be "organizations/[organization_id]/sources/[source_id]".

Parameters

findingId

string

Required. Unique identifier provided by the client within the parent scope. It must be alphanumeric and less than or equal to 32 characters and greater than 0 characters in length.

The request body contains an instance of [Finding](#)

(</security-command-center/docs/reference/rest/v1/organizations.sources.findings#create/>).

If successful, the response body contains a newly created instance of **Finding** (</security-command-center/docs/reference/rest/v1/organizations.sources.findings#Finding>).

Requires the following OAuth scope:

- <https://www.googleapis.com/auth/cloud-platform>

For more information, see the [Authentication Overview](https://cloud.google.com/docs/authentication/) (<https://cloud.google.com/docs/authentication/>).

Requires the following [Cloud IAM](https://cloud.google.com/iam/docs) (<https://cloud.google.com/iam/docs>) permission on the **parent** resource:

- `securitycenter.findings.update`

For more information, see the [Cloud IAM Documentation](https://cloud.google.com/iam/docs) (<https://cloud.google.com/iam/docs>).