

[Management Tools](https://cloud.google.com/products/management/) (https://cloud.google.com/products/management/)

[Cloud Shell](https://cloud.google.com/shell/) (https://cloud.google.com/shell/) [Documentation](#)

WaitOperationRequest

The request message for `Operations.WaitOperation`.

JSON representation

```
{
  "name": string,
  "timeout": string
}
```

Fields

name	string The name of the operation resource to wait on.
timeout	string (<u>Duration</u> (https://developers.google.com/protocol-buffers/docs/reference/google.protobuf#google.protobuf.Duration) format) The maximum duration to wait before timing out. If left blank, the wait will be at most the time permitted by the underlying HTTP/RPC protocol. If RPC context deadline is also specified, the shorter one will be used. A duration in seconds with up to nine fractional digits, terminated by 's'. Example: "3.5s".

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 4.0 License](https://creativecommons.org/licenses/by/4.0/) (https://creativecommons.org/licenses/by/4.0/), and code samples are licensed under the [Apache 2.0 License](https://www.apache.org/licenses/LICENSE-2.0) (https://www.apache.org/licenses/LICENSE-2.0). For details, see our [Site Policies](https://developers.google.com/terms/site-policies) (https://developers.google.com/terms/site-policies). Java is a registered trademark of Oracle and/or its affiliates.

Last updated April 9, 2019.