Cloud SQL (https://cloud.google.com/sql/)

Documentation (https://cloud.google.com/sql/docs/)

MySQL (https://cloud.google.com/sql/docs/mysql/) Reference

Method: backupRuns.list

Lists all backup runs associated with a given instance and configuration in the reverse chronological order of the backup initiation time.

HTTP request

```
GET
https://www.googleapis.com/sql/v1beta4/projects/{project}/instances/{instance}/backu
pRuns
```

The URL uses gRPC Transcoding
 (https://github.com/googleapis/googleapis/blob/master/google/api/http.proto) syntax.

Path parameters

Parameters	
project	string Project ID of the project that contains the instance.
instance	string Cloud SQL instance ID. This does not include the project ID.

Query parameters

Parameters	
maxResults	integer Maximum number of backup runs per response.

Parameters	
pageToken	**string** A previously-returned page token representing part of the larger set of results to view.

Request body

The request body must be empty.

Response body

If successful, the response body contains data with the following structure:

Backup run list results.

JSON representation
```{   "kind": string,   "items": [{   object (BackupRun (https://cloud.google.com/sql/docs/mysql/admin-api/rest/v1beta4/backupRu   }   ],   "nextPageToken": string }```

Fields	
kind	**string** This is always **sql#backupRunsList** .

Fields	
items[]	object (BackupRun (https://cloud.google.com/sql/docs/mysql/admin-api/rest/v1beta4/backupRuns#BackupRun)) A list of backup runs in reverse chronological order of the enqueued time.
nextPageToken	string The continuation token, used to page through large result sets. Provide this value in a subsequent request to return the next page of results.

Authorization Scopes

Requires one of the following OAuth scopes:

- https://www.googleapis.com/auth/cloud-platform
- https://www.googleapis.com/auth/sqlservice.admin

For more information, see the Authentication Overview (https://cloud.google.com/docs/authentication/).