Cloud SQL (https://cloud.google.com/sql/)
Documentation (https://cloud.google.com/sql/docs/)
MySQL (https://cloud.google.com/sql/docs/mysql/) Reference

Method: instances.listServerCas

Lists all of the trusted Certificate Authorities (CAs) for the specified instance. There can be up to three CAs listed: the CA that was used to sign the certificate that is currently in use, a CA that has been added but not yet used to sign a certificate, and a CA used to sign a certificate that has previously rotated out.

HTTP request

```
GET
https://www.googleapis.com/sql/v1beta4/projects/{project}/instances/{instance}/listS
erverCas
```

The URL uses gRPC Transcoding
 (https://github.com/googleapis/googleapis/blob/master/google/api/http.proto) syntax.

Path parameters

Parameters	
project	string Project ID of the project that contains the instance.
instance	string Cloud SQL instance ID. This does not include the project ID.

Request body

The request body must be empty.

Response body

If successful, the response body contains data with the following structure:

Instances instances.listServerCas response.

JSON representation
| ```
{
  "certs": [
    {
      object (SslCert (https://cloud.google.com/sql/docs/mysql/admin-api/rest/v1beta4/sslCerts#Ss
    }
  ],
  "activeVersion": string,
  "kind": string
}
``` |

Fields	
certs[]	**object (SslCert** (https://cloud.google.com/sql/docs/mysql/admin-api/rest/v1beta4/sslCerts#SslCert) **)** backupRuns.list of server CA certificates for the instance.
activeVersion	**string**
kind	**string** This is always **sql#instancesListServerCas** .

Authorization Scopes

Requires one of the following OAuth scopes:

- **https://www.googleapis.com/auth/cloud-platform**

- **https://www.googleapis.com/auth/sqlservice.admin**

For more information, see the Authentication Overview
(https://cloud.google.com/docs/authentication/).