

[Cloud SQL](https://cloud.google.com/sql/) (<https://cloud.google.com/sql/>)

[Documentation](https://cloud.google.com/sql/docs/) (<https://cloud.google.com/sql/docs/>)

[MySQL](https://cloud.google.com/sql/docs/mysql/) (<https://cloud.google.com/sql/docs/mysql/>) [Reference](#)



Method: instances.restart

Restarts a Cloud SQL instance.

HTTP request

POST

```
https://www.googleapis.com/sql/v1beta4/projects/{project}/instances/{instance}/restart
```

The URL uses [gRPC Transcoding](https://github.com/googleapis/googleapis/blob/master/google/api/http.proto)

(<https://github.com/googleapis/googleapis/blob/master/google/api/http.proto>) syntax.

Path parameters

Parameters

project	string Project ID of the project that contains the instance to be restarted.
instance	string Cloud SQL instance ID. This does not include the project ID.

Request body

The request body must be empty.

Response body

If successful, the response body contains an instance of [Operation](#)

(<https://cloud.google.com/sql/docs/mysql/admin-api/rest/v1beta4/operations#Operation>).

Authorization Scopes

Requires one of the following OAuth scopes:

- <https://www.googleapis.com/auth/cloud-platform>
- <https://www.googleapis.com/auth/sqlservice.admin>

For more information, see the [Authentication Overview](#)

(<https://cloud.google.com/docs/authentication/>).

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 4.0 License](https://creativecommons.org/licenses/by/4.0/) (<https://creativecommons.org/licenses/by/4.0/>), and code samples are licensed under the [Apache 2.0 License](https://www.apache.org/licenses/LICENSE-2.0) (<https://www.apache.org/licenses/LICENSE-2.0>). For details, see our [Site Policies](https://developers.google.com/terms/site-policies) (<https://developers.google.com/terms/site-policies>). Java is a registered trademark of Oracle and/or its affiliates.

Last updated December 9, 2019.