

[Cloud SQL](https://cloud.google.com/sql/) (https://cloud.google.com/sql/)

[Documentation](https://cloud.google.com/sql/docs/) (https://cloud.google.com/sql/docs/)

[MySQL](https://cloud.google.com/sql/docs/mysql/) (https://cloud.google.com/sql/docs/mysql/) [Reference](#)



Method: instances.truncateLog

Truncate MySQL general and slow query log tables

HTTP request

POST

`https://www.googleapis.com/sql/v1beta4/projects/{project}/instances/{instance}/truncateLog`

The URL uses [gRPC Transcoding](https://github.com/googleapis/googleapis/blob/master/google/api/http.proto)

(https://github.com/googleapis/googleapis/blob/master/google/api/http.proto) syntax.

Path parameters

Parameters	
project	string Project ID of the Cloud SQL project.
instance	string Cloud SQL instance ID. This does not include the project ID.

Request body

The request body contains an instance of **`InstancesTruncateLogRequest`**

(https://cloud.google.com/sql/docs/mysql/admin-api/rest/v1beta4/instances/truncateLog#InstancesTruncateLogRequest)

.

Response body

If successful, the response body contains an instance of [Operation](#) (<https://cloud.google.com/sql/docs/mysql/admin-api/rest/v1beta4/operations#Operation>).

Authorization Scopes

Requires one of the following OAuth scopes:

- <https://www.googleapis.com/auth/cloud-platform>
- <https://www.googleapis.com/auth/sqlservice.admin>

For more information, see the [Authentication Overview](#) (<https://cloud.google.com/docs/authentication/>).

InstancesTruncateLogRequest

Instance truncate log request.

JSON representation

```
{
  "truncateLogContext": {
    object (TruncateLogContext (https://cloud.google.com/sql/docs/mysql/admin-api/rest/v1beta4/i
  )
}
```

Fields

truncateLogContext	object (TruncateLogContext (https://cloud.google.com/sql/docs/mysql/admin-api/rest/v1beta4/instances/truncateLog#TruncateLogContext) Contains details about the truncate log operation.
---------------------------	---

TruncateLogContext

Database Instance truncate log context.

JSON representation

```
{
  "kind": string,
  "logType": string
}
```

Fields

kind**string**

This is always

sql#truncateLogContext

.

logType**string**

The type of log to truncate. Valid values are

MYSQL_GENERAL_TABLE

and

MYSQL_SLOW_TABLE

.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 4.0 License](https://creativecommons.org/licenses/by/4.0/) (https://creativecommons.org/licenses/by/4.0/), and code samples are licensed under the [Apache 2.0 License](https://www.apache.org/licenses/LICENSE-2.0) (https://www.apache.org/licenses/LICENSE-2.0). For details, see our [Site Policies](https://developers.google.com/terms/site-policies) (https://developers.google.com/terms/site-policies). Java is a registered trademark of Oracle and/or its affiliates.

Last updated December 9, 2019.