Cloud SQL (https://cloud.google.com/sql/)
Documentation (https://cloud.google.com/sql/docs/)
MySQL (https://cloud.google.com/sql/docs/mysql/) Reference

Method: users.list

Lists users in the specified Cloud SQL instance.

HTTP request

GET
`https://www.googleapis.com/sql/v1beta4/projects/{project}/instances/{instance}/users`

The URL uses gRPC Transcoding
 (https://github.com/googleapis/googleapis/blob/master/google/api/http.proto) syntax.

Path parameters

Parameters	
`project`	**string** Project ID of the project that contains the instance.
`instance`	**string** Database instance ID. This does not include the project ID.

Request body

The request body must be empty.

Response body

If successful, the response body contains data with the following structure:

User list response.

JSON representation

```
{
  "kind": string,
  "items": [
    {
      object (User (https://cloud.google.com/sql/docs/mysql/admin-api/rest/v1beta4/users#User))
    }
  ],
  "nextPageToken": string
}
```

Fields

kind	string
	This is always
	sql#usersList
	.
items[]	object (User (https://cloud.google.com/sql/docs/mysql/admin-api/rest/v1beta4/users#User))
	backupRuns.list of user resources in the instance.
nextPageToken	string
	An identifier that uniquely identifies the operation. You can use this identifier to retrieve the Operations resource that has information about the operation.

Authorization Scopes

Requires one of the following OAuth scopes:

- **https://www.googleapis.com/auth/cloud-platform**

- **https://www.googleapis.com/auth/sqlservice.admin**

For more information, see the Authentication Overview
(https://cloud.google.com/docs/authentication/).