


This page describes how to set up the Requester Pays feature and gives an example of making a request on a bucket that has enabled the Requester Pays feature. For a description of this feature, see [Requester Pays \(/storage/docs/requester-pays\)](/storage/docs/requester-pays).


The following sections show how to turn Requester Pays on and off, as well as how to check to see if Requester Pays is enabled on a bucket.


1. You should have the `storage.buckets.get` permission, which allows you to get the requester pays status for a bucket and is also required for enabling and disabling Requester Pays with the Google Cloud Console or gsutil.
2. When enabling or disabling Requester Pays, you must have the `storage.buckets.update` permission.
3. When disabling Requester Pays, you must either include a billing project in your request or else have the `resourcemanager.projects.createBillingAssignment` permission. See [Requester Pays Use and access requirements \(/storage/docs/requester-pays#requirements\)](/storage/docs/requester-pays#requirements) for more information.


Permissions are granted to users through [roles \(/storage/docs/access-control/iam#roles\)](/storage/docs/access-control/iam#roles). For example, users with `roles/storage.admin` have all of the above `storage.buckets` permissions. Roles can be [added to the project \(/storage/docs/access-control/using-iam-permissions#project-add\)](/storage/docs/access-control/using-iam-permissions#project-add) that contains the bucket.


To enable Requester Pays on a bucket:






















To disable Requester Pays on a bucket:



















To check whether Requester Pays is enabled on a bucket:














The following example shows how to include a billing project so that you can download an object (/storage/docs/downloading-objects) stored in a Requester Pays bucket. Use a similar procedure to perform other requests on the Requester Pays bucket or on objects within it. See Requester Pays access requirements (/storage/docs/requester-pays#requirements) for prerequisite considerations.

Important: Buckets that have Requester Pays disabled still accept requests that include a billing project, and charges are a billing project supplied in the request. Consider any billing implications prior to including a billing project in all of your requests.

