Job Search documentation

Method: projects.jobs.patch

Updates specified job.

Typically, updated contents become visible in search results within 10 seconds, but it may take up to 5 minutes.

HTTP request

PATCH https://jobs.googleapis.com/v4beta1/{job.name=projects/*/jobs/*}

The URL uses <u>gRPC Transcoding</u> (https://github.com/googleapis/googleapis/blob/master/google/api/http.proto) syntax.

Path parameters

Parameters

X

Parameters	
job.name	string
	Required during job update.
	The resource name for the job. This is generated by the service when a job is created.
	The format is "projects/{project_id}/tenants/{tenantId}/jobs/{job_id}". For example, "projects/foo/tenants/bar/jobs/baz".
	If tenant id is unspecified, the default tenant is used. For example, "projects/foo/jobs/bar".
	Use of this field in job queries and API calls is preferred over the use of <u>requisitionId</u> (https://cloud.google.com/talent-solution/job-
	search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.requisitionid) since this value is unique.

Request body

The request body contains data with the following structure:

JSON representation	
<pre>Son representation { "job": { "name": string, "company": string, "requisitionId": string, "title": string, "description": string, "addresses": [</pre>	
<pre>string], "applicationInfo": { "emails": [string], "instruction": string,</pre>	

```
JSON representation
       "uris": [
         string
      1
    },
     "jobBenefits": [
      enum (JobBenefit (https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4be
    1,
    "compensationInfo": {
       "entries": [
         {
           object (CompensationEntry (https://cloud.google.com/talent-solution/job-search/docs/ref
         }
      ],
       "annualizedBaseCompensationRange": {
         object (CompensationRange (https://cloud.google.com/talent-solution/job-search/docs/refere
      },
       "annualizedTotalCompensationRange": {
         object (CompensationRange (https://cloud.google.com/talent-solution/job-search/docs/refere
      }
    },
    "customAttributes": {
       "key": string,
       "value": {
         object (CustomAttribute)
      }
    },
    "degreeTypes": [
      enum (DegreeType (https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4be
    ],
    "department": string,
    "employmentTypes": [
      enum (EmploymentType (https://cloud.google.com/talent-solution/job-search/docs/reference/rest,
    ],
    "incentives": string,
    "languageCode": string,
    "jobLevel": enum (JobLevel (https://cloud.google.com/talent-solution/job-search/docs/reference
    "promotionValue": number,
    "qualifications": string,
    "responsibilities": string,
    "postingRegion": enum (PostingRegion(https://cloud.google.com/talent-solution/job-search/dc
    "visibility": enum (Visibility (https://cloud.google.com/talent-solution/job-search/docs/refe
    "jobStartTime": {
       "seconds": string,
```

JSON representation

```
"nanos": number
    },
    "jobEndTime": {
      "seconds": string,
      "nanos": number
    },
    "postingPublishTime": {
      "seconds": string,
      "nanos": number
    },
    "postingExpireTime": {
      "seconds": string,
      "nanos": number
    },
    "postingCreateTime": {
      "seconds": string,
      "nanos": number
    }.
    "postingUpdateTime": {
      "seconds": string,
      "nanos": number
    },
    "companyDisplayName": string,
    "derivedInfo": {
      "locations": [
        {
          object (Location (https://cloud.google.com/talent-solution/job-search/docs/reference/rest,
        }
      ],
      "jobCategories": [
        enum (JobCategory (https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v
      1
    },
    "processingOptions": {
      "disableStreetAddressResolution": boolean,
      "htmlSanitization": enum (HtmlSanitization(https://cloud.google.com/talent-solution/job-
    }
  },
  "updateMask": string
}
```

Fields	
job.company	<pre>string Required. The resource name of the company listing the job. The format is "projects/{project_id}/tenants/{tenantId}/companies/{company_id}". For example, "projects/foo/tenants/bar/companies/baz". If tenant id is unspecified, the default tenant is used. For example, "projects/foo/companies/bar".</pre>
job.requisitionId	<pre>string Required. The requisition ID, also referred to as the posting ID, is assigned by the client to identify a job. This field is intended to be used by clients for client identification and tracking of postings. A job isn't allowed to be created if there is another job with the same <u>company</u> (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.name) , <u>languageCode</u> (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.languag e_code) and <u>requisitionId</u> (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.languag e_code) and requisitionId (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.requisition n_id) . The maximum number of allowed characters is 255.</pre>
job.title	string Required. The title of the job, such as "Software Engineer" The maximum number of allowed characters is 500.

Fields	
job.description	<pre>string Required. The description of the job, which typically includes a multi- paragraph description of the company and related information. Separate fields are provided on the job object for <u>responsibilities</u> (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.responsi bilities) , <u>qualifications</u> (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.qualifica tions) , and other job characteristics. Use of these separate job fields is recommended. This field accepts and sanitizes HTML input, and also accepts bold, italic, ordered list, and unordered list markup tags. The maximum number of allowed characters is 100,000.</pre>

Fields	
job.addresses[]	string
	Strongly recommended for the best service experience.
	Location(s) where the employer is looking to hire for this job posting.
	Specifying the full street address(es) of the hiring location enables better API results, especially job searches by commute time.
	At most 50 locations are allowed for best search performance. If a job has more locations, it is suggested to split it into multiple jobs with unique <u>requisitionId</u>
	(https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.requisitio n_id)
	s (e.g. 'ReqA' becomes 'ReqA-1', 'ReqA-2', and so on.) as multiple jobs with the same <u>company</u>
	(https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.compan y)
	, <u>languageCode</u> (https://cloud.google.com/talent-solution/job-
	search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.languag e_code)
	and <u>requisitionId</u>
	(https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.requisitio n_id)
	are not allowed. If the original <u>requisitionId</u> (https://cloud.google.com/talent-solution/job-
	search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.requisitio n_id)
	must be preserved, a custom field should be used for storage. It is also suggested to group the locations that close to each other in the same job for better search experience.
	The maximum number of allowed characters is 500.

Fields	
job.applicationInfo	<pre>object (ApplicationInfo (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job.ApplicationInfo)) Job application information.</pre>
job.jobBenefits[]	enum (JobBenefit (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job.JobBenefit)) The benefits included with the job.
job.compensationInfo	object (CompensationInfo (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job.CompensationIn fo)) Job compensation information (a.k.a. "pay rate") i.e., the compensation that will paid to the employee.
job.customAttributes	 map (key: string, value: object (CustomAttribute)) A map of fields to hold both filterable and non-filterable custom job attributes that are not covered by the provided structured fields. The keys of the map are strings up to 64 bytes and must match the pattern: [a-zA-Z][a-zA-Z0-9_]*. For example, key0LikeThis or KEY_1_LIKE_THIS. At most 100 filterable and at most 100 unfilterable keys are supported. For filterable stringValues, across all keys at most 200 values are allowed, with each string no more than 255 characters. For unfilterable stringValues, the maximum total size of stringValues across all keys is 50KB.

Fields	
job.degreeTypes[]	enum (<u>DegreeType</u> (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/DegreeType)) The desired education degrees for the job, such as Bachelors, Masters.
job.department	string The department or functional area within the company with the open position. The maximum number of allowed characters is 255.
job.employmentTypes[]	<pre>enum (EmploymentType (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job.EmploymentTyp e)) The employment type(s) of a job, for example, full time (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job.EmploymentTyp e.ENUM_VALUES.FULL_TIME) or part time (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job.EmploymentTyp e.ENUM_VALUES.FULL_TIME)</pre>
job.incentives	string A description of bonus, commission, and other compensation incentives associated with the job not including salary or pay. The maximum number of allowed characters is 10,000.

Fields	
job.languageCode	string
	The language of the posting. This field is distinct from any requirements for fluency that are associated with the job.
	Language codes must be in BCP-47 format, such as "en-US" or "sr-Latn". For more information, see <u>Tags for Identifying Languages</u> (https://tools.ietf.org/html/bcp47){: class="external" target="_blank" }.
	If this field is unspecified and <u>Job.description</u> (https://cloud.google.com/talent-solution/job-
	search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.descripti on)
	is present, detected language code based on <u>Job.description</u> (https://cloud.google.com/talent-solution/job-
	search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.descripti on)
	is assigned, otherwise defaults to 'en_US'.
job.jobLevel	enum (<u>JobLevel</u> (https://cloud.google.com/talent-solution/job-
	search/docs/reference/rest/v4beta1/projects.jobs#Job.JobLevel))
	The experience level associated with the job, such as "Entry Level".
job.promotionValue	number
	A promotion value of the job, as determined by the client. The value determines the sort order of the jobs returned when searching for jobs using the featured jobs search call, with higher promotional values being returned first and ties being resolved by relevance sort. Only the jobs with a promotionValue >0 are returned in a FEATURED_JOB_SEARCH.
	Default value is 0, and negative values are treated as 0.

job.qualifications	string
	A description of the qualifications required to perform the job. The use of this field is recommended as an alternative to using the more general description (https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.descript on) field. This field accepts and sanitizes HTML input, and also accepts bold, italic, ordered list, and unordered list markup tags. The maximum number of allowed characters is 10,000.
job.responsibilities	string A description of job responsibilities. The use of this field is recommended as an alternative to using the more general description (https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.descript on) field. This field accepts and sanitizes HTML input, and also accepts bold, italic,
	ordered list, and unordered list markup tags. The maximum number of allowed characters is 10,000.

Fields	
job.postingRegion	<pre>enum (PostingRegion (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job.PostingRegion)) The job PostingRegion (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job.PostingRegion) (for example, state, country) throughout which the job is available. If this field is set, a LocationFilter (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/LocationFilter) in a search query within the job region finds this job posting if an exact location match isn't specified. If this field is set to PostingRegion.NATION (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job.PostingRegion.E NUM_VALUES.NATION) or PostingRegion.ADMINISTRATIVE_AREA (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job.PostingRegion.E NUM_VALUES.ADMINISTRATIVE_AREA) , setting job Job.addresses (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job.PostingRegion.E NUM_VALUES.ADMINISTRATIVE_AREA) , setting job Job.addresses (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.addresses s) to the same location level as this field is strongly recommended.</pre>
job.visibility (deprecated)	<pre>enum (Visibility (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job.Visibility)) Deprecated. The job is only visible to the owner. The visibility of the job. Defaults to Visibility.ACCOUNT_ONLY (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job.Visibility.ENUM_ VALUES.ACCOUNT_ONLY) if not specified.</pre>

Fields	
job.jobStartTime	string (<u>Timestamp</u> (https://developers.google.com/protocol- buffers/docs/reference/google.protobuf#google.protobuf.Timestamp) format) The start timestamp of the job in UTC time zone. Typically this field is used
	for contracting engagements. Invalid timestamps are ignored.
job.jobEndTime	<pre>string (<u>Timestamp</u> (https://developers.google.com/protocol- buffers/docs/reference/google.protobuf#google.protobuf.Timestamp) format)</pre>
	The end timestamp of the job. Typically this field is used for contracting engagements. Invalid timestamps are ignored.
job.postingPublishTime	<pre>string (<u>Timestamp</u> (https://developers.google.com/protocol- buffers/docs/reference/google.protobuf#google.protobuf.Timestamp) format)</pre>
	The timestamp this job posting was most recently published. The default value is the time the request arrives at the server. Invalid timestamps are ignored.
job.postingExpireTime	<pre>string (<u>Timestamp</u> (https://developers.google.com/protocol- buffers/docs/reference/google.protobuf#google.protobuf.Timestamp) format)</pre>
	Strongly recommended for the best service experience.
	The expiration timestamp of the job. After this timestamp, the job is marked as expired, and it no longer appears in search results. The expired job can't be listed by the jobs.list (https://cloud.google.com/talent-solution/job-
	<pre>search/docs/reference/rest/v4beta1/projects.tenants.jobs/list#google. oud.talent.v4beta1.JobService.ListJobs) API, but it can be retrieved with the jobs.get (https://cloud.google.com/talent-solution/job-</pre>
	search/docs/reference/rest/v4beta1/projects.tenants.jobs/get#google. oud.talent.v4beta1.JobService.GetJob) API or updated with the j <u>obs.patch</u>

Fields

(https://cloud.go	ogle.com/talent-solution/job-
search/docs/refe	erence/rest/v4beta1/projects.tenants.jobs/patch#googl
e.cloud.talent.v4	beta1.JobService.UpdateJob)
API or deleted wit	h the jobs.delete
(https://cloud.go	ogle.com/talent-solution/job-
search/docs/refe	erence/rest/v4beta1/projects.tenants.jobs/delete#googl
e.cloud.talent.v4	beta1.JobService.DeleteJob)
API. An expired jo	b can be updated and opened again by using a future
expiration timest	amp. Updating an expired job fails if there is another
existing open job	with same <u>company</u>
(https://cloud.go	ogle.com/talent-solution/job-
search/docs/refe	erence/rest/v4beta1/projects.jobs#Job.FIELDS.compan
y)	
, <u>languageCode</u>	
	ogle.com/talent-solution/job-
search/docs/refe	erence/rest/v4beta1/projects.jobs#Job.FIELDS.languag
e_code)	
and <u>requisitio</u>	<u>nId</u>
(https://cloud.go	ogle.com/talent-solution/job-
search/docs/refe	erence/rest/v4beta1/projects.jobs#Job.FIELDS.requisition
n_id)	
The expired ions :	are retained in our system for 90 days. However, the
	count cannot exceed 3 times the maximum number of
• •	evious 7 days. If this threshold is exceeded, expired jobs
	order of earliest expire time. Expired jobs are no longer
	hey are cleaned out.
Invalid timestam	os are ignored, and treated as expire time not provided.
If the timestamp	is before the instant request is made, the job is treated as
•	ely on creation. This kind of job can not be updated. And
•	ob with past timestamp, the postingPublishTime
	ogle.com/talent-solution/job-
	erence/rest/v4beta1/projects.jobs#Job.FIELDS.posting_
publish_time)	
	e <u>postingExpireTime</u>
	ogle.com/talent-solution/job-
	erence/rest/v4beta1/projects.jobs#Job.FIELDS.posting_
expire_time)	· · · · · · · · · · · · · · · · · · ·
• •	his feature is to allow other objects, such as
<u>Application</u>	

Fields	
	<pre>(https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.tenants.profiles.applicatio ns#Application) , to refer a job that didn't exist in the system prior to becoming expired. If you want to modify a job that was expired on creation, delete it and create a new one. If this value isn't provided at the time of job creation or is invalid, the job posting expires after 30 days from the job's creation time. For example, if the job was created on 2017/01/01 13:00AM UTC with an unspecified expiration date, the job expires after 2017/01/31 13:00AM UTC. If this value isn't provided on job update, it depends on the field masks set by <u>Update_JobRequest.update_mask</u> (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.tenants.jobs/patch#body.r equest_body.FIELDS.update_mask) . If the field masks include jobEndTime (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.job_end_ time) , or the masks are empty meaning that every field is updated, the job posting expires after 30 days from the job's last update time. Otherwise the expiration date isn't updated.</pre>
job.postingCreateTime	<pre>string (<u>Timestamp</u> (https://developers.google.com/protocol- buffers/docs/reference/google.protobuf#google.protobuf.Timestamp) format) Output only. The timestamp when this job posting was created.</pre>
job.postingUpdateTime	<pre>string (<u>Timestamp</u> (https://developers.google.com/protocol- buffers/docs/reference/google.protobuf#google.protobuf.Timestamp) format) Output only. The timestamp when this job posting was last updated.</pre>
job.companyDisplayName	string Output only. Display name of the company listing the job.

Fields	
job.derivedInfo	<pre>object (DerivedInfo (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job.DerivedInfo)) Output only. Derived details about the job posting.</pre>
job.processingOptions	object (<u>ProcessingOptions</u> (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job.ProcessingOptions)) Options for job processing.
updateMask	<pre>string (FieldMask (https://developers.google.com/protocol- buffers/docs/reference/google.protobuf#google.protobuf.FieldMask) format) Strongly recommended for the best service experience. If <u>updateMask</u> (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.tenants.jobs/patch#body. equest_body.FIELDS.update_mask) is provided, only the specified fields in job are updated. Otherwise all the fields are updated. A field mask to restrict the fields that are updated. Only top level fields of <u>Job</u> (https://cloud.google.com/talent-solution/job- search/docs/reference/rest/v4beta1/projects.jobs#Job) are supported. A comma-separated list of fully qualified names of fields. Example: "user.displayName, photo".</pre>

Response body

If successful, the response body contains an instance of <u>Job</u>

(https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job).

Authorization Scopes

Requires one of the following OAuth scopes:

- https://www.googleapis.com/auth/jobs
- https://www.googleapis.com/auth/cloud-platform

For more information, see the <u>Authentication Overview</u> (https://cloud.google.com/docs/authentication/).

Except as otherwise noted, the content of this page is licensed under the <u>Creative Commons Attribution 4.0 License</u> (https://creativecommons.org/licenses/by/4.0/), and code samples are licensed under the <u>Apache 2.0 License</u> (https://www.apache.org/licenses/LICENSE-2.0). For details, see our <u>Site Policies</u> (https://developers.google.com/terms/site-policies). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 15, 2019.