

[Job Search documentation](#)

# Method: projects.jobs.search



Searches for jobs using the provided `SearchJobsRequest`.

This call constrains the visibility

(<https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.visibility>)

of jobs present in the database, and only returns jobs that the caller has permission to search against.

## HTTP request

**POST** `https://jobs.googleapis.com/v4beta1/{parent=projects/*}/jobs:search`

The URL uses gRPC Transcoding

(<https://github.com/googleapis/googleapis/blob/master/google/api/http.proto>) syntax.

## Path parameters

### Parameters

**parent**

**string**

Required. The resource name of the tenant to search within.

The format is "projects/{project\_id}/tenants/{tenantId}". For example, "projects/foo/tenant/bar". If tenant id is unspecified, a default tenant is created. For example, "projects/foo".

## Request body

The request body contains data with the following structure:

### JSON representation

```
{
  "searchMode": enum (SearchMode (https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs/search)),
  "requestMetadata": {
    object (RequestMetadata (https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs/search))
  },
  "jobQuery": {
    object (JobQuery (https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs/search))
  },
  "enableBroadening": boolean,
  "requirePreciseResultSize": boolean,
  "histogramQueries": [
    {
      object (HistogramQuery (https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs/search))
    }
  ],
  "jobView": enum (JobView (https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs/search)),
  "offset": number,
  "pageSize": number,
  "pageToken": string,
  "orderBy": string,
  "diversificationLevel": enum (DiversificationLevel (https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs/search)),
  "customRankingInfo": {
    object (CustomRankingInfo (https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs/search))
  },
  "disableKeywordMatch": boolean
}
```

### Fields

Fields	
<b>searchMode</b>	<p><b>enum</b> (<b><u>SearchMode</u></b> (<a href="https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/SearchMode">https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/SearchMode</a>) )</p> <p>Mode of a search.</p> <p>Defaults to <b><u>SearchMode.JOB_SEARCH</u></b> (<a href="https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/SearchMode#ENUM_VALUES.JOB_SEARCH">https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/SearchMode#ENUM_VALUES.JOB_SEARCH</a>) .</p>
<b>requestMetadata</b>	<p><b>object</b> (<b><u>RequestMetadata</u></b> (<a href="https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/RequestMetadata">https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/RequestMetadata</a>) )</p> <p>Required. The meta information collected about the job searcher, used to improve the search quality of the service. The identifiers (such as <b>userId</b>) are provided by users, and must be unique and consistent.</p>
<b>jobQuery</b>	<p><b>object</b> (<b><u>JobQuery</u></b> (<a href="https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/JobQuery">https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/JobQuery</a>) )</p> <p>Query used to search against jobs, such as keyword, location filters, etc.</p>
<b>enableBroadening</b>	<p><b>boolean</b></p> <p>Controls whether to broaden the search when it produces sparse results. Broadened queries append results to the end of the matching results list.</p> <p>Defaults to false.</p>

## Fields

<b>requirePreciseResultSize</b>	<b>boolean</b>  Controls if the search job request requires the return of a precise count of the first 300 results. Setting this to <b>true</b> ensures consistency in the number of results per page. Best practice is to set this value to true if a client allows users to jump directly to a non-sequential search results page.  Enabling this flag may adversely impact performance.  Defaults to false.
<b>histogramQueries[]</b>	<b>object</b> ( <a href="https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/HistogramQuery">HistogramQuery</a> ( <a href="https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/HistogramQuery">https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/HistogramQuery</a> ) )  An expression specifies a histogram request against matching jobs.  Expression syntax is an aggregation function call with histogram facets and other options.  Available aggregation function calls are: * <b>count(string_histogram_facet)</b> : Count the number of matching entities, for each distinct attribute value. * <b>count(numeric_histogram_facet, list of buckets)</b> : Count the number of matching entities within each bucket.  Data types: <ul style="list-style-type: none"> <li>• Histogram facet: facet names with format [a-zA-Z][a-zA-Z0-9_]+.</li> <li>• String: string like "any string with backslash escape for quote(\\)".</li> <li>• Number: whole number and floating point number like 10, -1 and -0.01.</li> <li>• List: list of elements with comma(,) separator surrounded by square brackets, for example, [1, 2, 3] and ["one", "two", "three"].</li> </ul> Built-in constants: <ul style="list-style-type: none"> <li>• MIN (minimum number similar to java Double.MIN_VALUE)</li> <li>• MAX (maximum number similar to java Double.MAX_VALUE)</li> </ul> Built-in functions:

## Fields

- `bucket(start, end[, label])`: bucket built-in function creates a bucket with range of `[start, end)`. Note that the end is exclusive, for example, `bucket(1, MAX, "positive number")` or `bucket(1, 10)`.

### Job histogram facets:

- `companyDisplayName`: histogram by `Job.company_display_name` ([https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.company\\_display\\_name](https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.company_display_name))
- `employment_type`: histogram by `Job.employment_types` ([https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.employment\\_types](https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.employment_types)), for example, "FULL\_TIME", "PART\_TIME".
- `companySize`: histogram by `CompanySize` (<https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.companies#Company.CompanySize>), for example, "SMALL", "MEDIUM", "BIG".
- `publish_time_in_month`: histogram by the `Job.posting_publish_time` ([https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.posting\\_publish\\_time](https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.posting_publish_time)) in months. Must specify list of numeric buckets in spec.
- `publish_time_in_year`: histogram by the `Job.posting_publish_time` ([https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.posting\\_publish\\_time](https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.posting_publish_time)) in years. Must specify list of numeric buckets in spec.
- `degreeTypes`: histogram by the `Job.degree_types` ([https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.degree\\_types](https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.degree_types)), for example, "Bachelors", "Masters".
- `jobLevel`: histogram by the `Job.job_level` ([https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.job\\_level](https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.job_level))

## Fields

- , for example, "Entry Level".
- **country**: histogram by the country code of jobs, for example, "US", "FR".
  - **admin1**: histogram by the admin1 code of jobs, which is a global placeholder referring to the state, province, or the particular term a country uses to define the geographic structure below the country level, for example, "CA", "IL".
  - **city**: histogram by a combination of the "city name, admin1 code". For example, "Mountain View, CA", "New York, NY".
  - **admin1\_country**: histogram by a combination of the "admin1 code, country", for example, "CA, US", "IL, US".
  - **city\_coordinate**: histogram by the city center's GPS coordinates (latitude and longitude), for example, 37.4038522,-122.0987765. Since the coordinates of a city center can change, customers may need to refresh them periodically.
  - **locale**: histogram by the **Job.language\_code** ([https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.language\\_code](https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.language_code)) , for example, "en-US", "fr-FR".
  - **language**: histogram by the language subtag of the **Job.language\_code** ([https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.language\\_code](https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.language_code)) , for example, "en", "fr".
  - **category**: histogram by the **JobCategory** (<https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.JobCategory>) , for example, "COMPUTER\_AND\_IT", "HEALTHCARE".
  - **base\_compensation\_unit**: histogram by the **CompensationInfo.CompensationUnit** (<https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.CompensationUnit>) of base salary, for example, "WEEKLY", "MONTHLY".
  - **base\_compensation**: histogram by the base salary. Must specify list of numeric buckets to group results by.

## Fields

- `annualized_base_compensation`: histogram by the base annualized salary. Must specify list of numeric buckets to group results by.
- `annualized_total_compensation`: histogram by the total annualized salary. Must specify list of numeric buckets to group results by.
- `string_custom_attribute`: histogram by string **Job.custom\_attributes** ([https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.custom\\_attributes](https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.custom_attributes))  
. Values can be accessed via square bracket notations like `string_custom_attribute["key1"]`.
- `numeric_custom_attribute`: histogram by numeric **Job.custom\_attributes** ([https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.custom\\_attributes](https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.custom_attributes))  
. Values can be accessed via square bracket notations like `numeric_custom_attribute["key1"]`. Must specify list of numeric buckets to group results by.

Example expressions:

- `count(admin1)`
- `count(base_compensation, [bucket(1000, 10000), bucket(10000, 100000), bucket(100000, MAX)])`
- `count(string_custom_attribute["some-string-custom-attribute"])`
- `count(numeric_custom_attribute["some-numeric-custom-attribute"], [bucket(MIN, 0, "negative"), bucket(0, MAX, "non-negative")])`

## Fields

<b>jobView</b>	<p><b>enum</b> (<a href="https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/JobView">JobView</a>) (<a href="https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/JobView">https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/JobView</a>) )</p> <p>The desired job attributes returned for jobs in the search response. Defaults to <a href="https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/JobView#ENUM_VALUES.JOB_VIEW_SMALL">JobView.JOB_VIEW_SMALL</a> (<a href="https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/JobView#ENUM_VALUES.JOB_VIEW_SMALL">https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/JobView#ENUM_VALUES.JOB_VIEW_SMALL</a>) if no value is specified.</p>
<b>offset</b>	<p><b>number</b></p> <p>An integer that specifies the current offset (that is, starting result location, amongst the jobs deemed by the API as relevant) in search results. This field is only considered if <a href="https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.tenants.jobs/search#body.request_body.FIELDS.page_token">pageToken</a> (<a href="https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.tenants.jobs/search#body.request_body.FIELDS.page_token">https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.tenants.jobs/search#body.request_body.FIELDS.page_token</a>) is unset.</p> <p>For example, 0 means to return results starting from the first matching job, and 10 means to return from the 11th job. This can be used for pagination, (for example, <code>pageSize = 10</code> and <code>offset = 10</code> means to return from the second page).</p>
<b>pageSize</b>	<p><b>number</b></p> <p>A limit on the number of jobs returned in the search results. Increasing this value above the default value of 10 can increase search response time. The value can be between 1 and 100.</p>
<b>pageToken</b>	<p><b>string</b></p> <p>The token specifying the current offset within search results. See <a href="https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/SearchJobsResponse#FIELDS.next_page_token">SearchJobsResponse.next_page_token</a> (<a href="https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/SearchJobsResponse#FIELDS.next_page_token">https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/SearchJobsResponse#FIELDS.next_page_token</a>) for an explanation of how to obtain the next set of query results.</p>
<b>orderBy</b>	<p><b>string</b></p>



## Fields

The criteria determining how search results are sorted. Default is "relevance desc".

Supported options are:

- "relevance desc": By relevance descending, as determined by the API algorithms. Relevance thresholding of query results is only available with this ordering.
- "postingPublishTime desc": By Job.posting\_publish\_time ([https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.posting\\_publish\\_time](https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.posting_publish_time)) descending.
- "postingUpdateTime desc": By Job.posting\_update\_time ([https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.posting\\_update\\_time](https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.posting_update_time)) descending.
- "title": By Job.title (<https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.title>) ascending.
- "title desc": By Job.title (<https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.title>) descending.
- "annualized\_base\_compensation": By job's CompensationInfo.annualized\_base\_compensation\_range ([https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.CompensationInfo.FIELDS.annualized\\_base\\_compensation\\_range](https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.CompensationInfo.FIELDS.annualized_base_compensation_range)) ascending. Jobs whose annualized base compensation is unspecified are put at the end of search results.
- "annualized\_base\_compensation desc": By job's CompensationInfo.annualized\_base\_compensation\_range ([https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.CompensationInfo.FIELDS.annualized\\_base\\_compensation\\_range](https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.CompensationInfo.FIELDS.annualized_base_compensation_range)) descending. Jobs whose annualized base compensation is unspecified are put at the end of search results.

## Fields

- **"annualized\_total\_compensation"**: By job's [CompensationInfo.annualized\\_total\\_compensation\\_range](https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.CompensationInfo.FIELDS.annualized_total_compensation_range) (https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.CompensationInfo.FIELDS.annualized\_total\_compensation\_range) ascending. Jobs whose annualized base compensation is unspecified are put at the end of search results.
- **"annualized\_total\_compensation\_desc"**: By job's [CompensationInfo.annualized\\_total\\_compensation\\_range](https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.CompensationInfo.FIELDS.annualized_total_compensation_range) (https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.CompensationInfo.FIELDS.annualized\_total\_compensation\_range) descending. Jobs whose annualized base compensation is unspecified are put at the end of search results.
- **"custom\_ranking\_desc"**: By the relevance score adjusted to the [SearchJobsRequest.CustomRankingInfo.ranking\\_expression](https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/CustomRankingInfo#FIELDS.ranking_expression) (https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/CustomRankingInfo#FIELDS.ranking\_expression) with weight factor assigned by [SearchJobsRequest.CustomRankingInfo.importance\\_level](https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/CustomRankingInfo#FIELDS.importance_level) (https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/CustomRankingInfo#FIELDS.importance\_level) in descending order.
- Location sorting: Use the special syntax to order jobs by distance:
  - "distance\_from('Hawaii')"**: Order by distance from Hawaii.
  - "distance\_from(19.89, 155.5)"**: Order by distance from a coordinate.
  - "distance\_from('Hawaii'), distance\_from('Puerto Rico')"**: Order by multiple locations. See details below.
  - "distance\_from('Hawaii'), distance\_from(19.89, 155.5)"**: Order by multiple locations. See details below.

The string can have a maximum of 256 characters. When multiple distance centers are provided, a job that is close to any of the distance centers would have a high rank. When a job has multiple locations, the job location closest to one of the distance centers will be used. Jobs that don't have locations will be ranked at the bottom. Distance is calculated with a precision of 11.3 meters (37.4 feet). Diversification strategy is still applied unless explicitly disabled in [diversificationLevel](#)

<b>Fields</b>	<p>(<a href="https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.tenants.jobs/search#body.request_body.FIELDS.diversification_level">https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.tenants.jobs/search#body.request_body.FIELDS.diversification_level</a>)</p>
<b>diversificationLevel</b>	<p>enum (<a href="https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/DiversificationLevel">DiversificationLevel</a>)</p> <p>(<a href="https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/DiversificationLevel">https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/DiversificationLevel</a>)</p> <p>)</p> <p>Controls whether highly similar jobs are returned next to each other in the search results. Jobs are identified as highly similar based on their titles, job categories, and locations. Highly similar results are clustered so that only one representative job of the cluster is displayed to the job seeker higher up in the results, with the other jobs being displayed lower down in the results.</p> <p>Defaults to <a href="https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/DiversificationLevel#ENUM_VALUES.SIMPLE">DiversificationLevel.SIMPLE</a> (<a href="https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/DiversificationLevel#ENUM_VALUES.SIMPLE">https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/DiversificationLevel#ENUM_VALUES.SIMPLE</a>) if no value is specified.</p>
<b>customRankingInfo</b>	<p>object (<a href="https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/CustomRankingInfo">CustomRankingInfo</a>)</p> <p>(<a href="https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/CustomRankingInfo">https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/CustomRankingInfo</a>)</p> <p>)</p> <p>Controls over how job documents get ranked on top of existing relevance score (determined by API algorithm).</p>
<b>disableKeywordMatch</b>	<p>boolean</p> <p>Controls whether to disable exact keyword match on <a href="https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.title">Job.title</a> (<a href="https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.title">https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.title</a>), <a href="https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.description">Job.description</a> (<a href="https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.description">https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.description</a>), <a href="https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.company_display_name">Job.company_display_name</a></p>

## Fields

([https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.company\\_display\\_name](https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.company_display_name))

, **Job.addresses**

(<https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.addresses>)

, **Job.qualifications**

(<https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.jobs#Job.FIELDS.qualifications>)

. When `disable_keyword_match` is turned off, a keyword match returns jobs that do not match given category filters when there are matching keywords. For example, for the query "program manager," a result is returned even if the job posting has the title "software developer," which doesn't fall into "program manager" ontology, but does have "program manager" appearing in its description.

For queries like "cloud" that don't contain title or location specific ontology, jobs with "cloud" keyword matches are returned regardless of this flag's value.

Use **Company.keyword\_searchable\_job\_custom\_attributes**

([https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.companies#Company.FIELDS.keyword\\_searchable\\_job\\_custom\\_attributes](https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.companies#Company.FIELDS.keyword_searchable_job_custom_attributes))

if company-specific globally matched custom field/attribute string values are needed. Enabling keyword match improves recall of subsequent search requests.

Defaults to false.

## Response body

If successful, the response body contains an instance of **SearchJobsResponse**

(<https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/SearchJobsResponse>).

## Authorization Scopes

Requires one of the following OAuth scopes:

- <https://www.googleapis.com/auth/jobs>
- <https://www.googleapis.com/auth/cloud-platform>

For more information, see the [Authentication Overview](https://cloud.google.com/docs/authentication/) (<https://cloud.google.com/docs/authentication/>).

---

*Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 4.0 License](https://creativecommons.org/licenses/by/4.0/) (<https://creativecommons.org/licenses/by/4.0/>), and code samples are licensed under the [Apache 2.0 License](https://www.apache.org/licenses/LICENSE-2.0) (<https://www.apache.org/licenses/LICENSE-2.0>). For details, see our [Site Policies](https://developers.google.com/terms/site-policies) (<https://developers.google.com/terms/site-policies>). Java is a registered trademark of Oracle and/or its affiliates.*

*Last updated September 13, 2019.*