Method: projects.tenants.profiles.list   :: ✕

Lists profiles by filter. The order is unspecified.

HTTP request

`GET https://jobs.googleapis.com/v4beta1/{parent=projects/*/tenants/*}/profiles`

The URL uses gRPC Transcoding
 (https://github.com/googleapis/googleapis/blob/master/google/api/http.proto) syntax.

Path parameters

Parameters	
parent	string Required. The resource name of the tenant under which the profile is created. The format is "projects/{project_id}/tenants/{tenantId}". For example, "projects/foo/tenants/bar".

Query parameters

Parameters	

Parameters	
filter	**string** The filter string specifies the profiles to be enumerated. Supported operator: =, AND The field(s) eligible for filtering are: • **externalId** • **groupId** externalId and groupId cannot be specified at the same time. If both externalId and groupId are provided, the API will return a bad request error. Sample Query: • externalId = "externalId-1" • groupId = "groupId-1"
pageToken	**string** The token that specifies the current offset (that is, starting result). Please set the value to **ListProfilesResponse.next_page_token** (https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.tenants.profiles/list#body.ListProfilesResponse.FIELDS.next_page_token) to continue the list.
pageSize	**number** The maximum number of profiles to be returned, at most 100. Default is 100 unless a positive number smaller than 100 is specified.

Parameters	
readMask	string (<u>FieldMask</u> (https://developers.google.com/protocol-buffers/docs/reference/google.protobuf#google.protobuf.FieldMask) format) A field mask to specify the profile fields to be listed in response. All fields are listed if it is unset. Valid values are: • `name` A comma-separated list of fully qualified names of fields. Example: `"user.displayName,photo"`.

Request body

The request body must be empty.

Response body

If successful, the response body contains data with the following structure:

The List profiles response object.

JSON representation
| ```
{
  "profiles": [
    {
      object (Profile (https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4bet
    }
  ],
  "nextPageToken": string
}
``` |

Fields

Fields	
`profiles[]`	object (Profile (https://cloud.google.com/talent-solution/job-search/docs/reference/rest/v4beta1/projects.tenants.profiles#Profile)) Profiles for the specific tenant.
`nextPageToken`	string A token to retrieve the next page of results. This is empty if there are no more results.

Authorization Scopes

Requires one of the following OAuth scopes:

- `https://www.googleapis.com/auth/jobs`

- `https://www.googleapis.com/auth/cloud-platform`

For more information, see the Authentication Overview (https://cloud.google.com/docs/authentication/).