

Starts asynchronous cancellation on a long-running operation. The server makes a best effort to cancel the operation, but success is not guaranteed. If the server doesn't support this method, it returns `google.rpc.Code.UNIMPLEMENTED`. Clients can use [Operations.GetOperation](#) (/video-intelligence/automl/docs/reference/rest/v1beta1/projects.locations.operations/get#google.longrunning.Operations.GetOperation)

or other methods to check whether the cancellation succeeded or whether the operation completed despite cancellation. On successful cancellation, the operation is not deleted; instead, it becomes an operation with an [Operation.error](#)

(/video-intelligence/automl/docs/reference/rest/v1beta1/projects.locations.operations#Operation.FIELDS.error) value with a [google.rpc.Status.code](#)

(/video-intelligence/automl/docs/reference/rest/v1beta1/projects.locations.operations#Status.FIELDS.code) of 1, corresponding to `Code.CANCELLED`.

POST <https://automl.googleapis.com/v1beta1/{name}:cancel>

#### Parameters

<b>name</b>	<b>string</b>
	The name of the operation resource to be cancelled.

The request body must be empty.

If successful, the response body will be empty.

Requires the following OAuth scope:

- <https://www.googleapis.com/auth/cloud-platform>

For more information, see the [Authentication Overview](https://cloud.google.com/docs/authentication/) (<https://cloud.google.com/docs/authentication/>).