

[Cloud AutoML Vision](#)

Method: projects.locations.models.undeploy

Undeploys a model. If the model is not deployed this method has no effect.

Only applicable for Image Object Detection and Image Classification; all other domains manage deployment automatically.

Returns an empty response in the **response**

(<https://cloud.google.com/vision/automl/docs/reference/rest/v1beta1/projects.locations.operations#Operation.FIELDS.response>)

field when it completes.

HTTP request

POST <https://automl.googleapis.com/v1beta1/{name}:undeploy>

Path parameters

Parameters

name	string Resource name of the model to undeploy. Authorization requires the following Google IAM (https://cloud.google.com/iam) permission on the specified resource name : <ul style="list-style-type: none"><code>automl.models.undeploy</code>
-------------	--

Request body

The request body must be empty.

Response body

If successful, the response body contains an instance of Operation

(<https://cloud.google.com/vision/automl/docs/reference/rest/v1beta1/projects.locations.operations#Operation>)

.

Authorization Scopes

Requires the following OAuth scope:

- <https://www.googleapis.com/auth/cloud-platform>

For more information, see the Authentication Overview

(<https://cloud.google.com/docs/authentication/>).

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 4.0 License (<https://creativecommons.org/licenses/by/4.0/>), and code samples are licensed under the Apache 2.0 License (<https://www.apache.org/licenses/LICENSE-2.0>). For details, see our Site Policies (<https://developers.google.com/terms/site-policies>). Java is a registered trademark of Oracle and/or its affiliates.

Last updated October 9, 2019.