

[Cloud AutoML Vision Object Detection](#)

REST Resource: projects.locations.operations

Resource: Operation

This resource represents a long-running operation that is the result of a network API call.

JSON representation

```
{
  "name": string,
  "metadata": {
    "@type": string,
    field1: ...,
    ...
  },
  "done": boolean,

  // Union field result can be only one of the following:
  "error": {
    object (Status (https://cloud.google.com/vision/automl/object-detection/docs/reference/rest/v1beta1
  ),
  "response": {
    "@type": string,
    field1: ...,
    ...
  }
  // End of list of possible types for union field result.
}
```

Fields

name	string
	The server-assigned name, which is only unique within the same service that originally returns it. If you use the default HTTP mapping, the name should be a resource name ending with operations/{unique_id} .

Fields

metadata

object

Service-specific metadata associated with the operation. It typically contains progress information and common metadata such as create time. Some services might not provide such metadata. Any method that returns a long-running operation should document the metadata type, if any.

An object containing fields of an arbitrary type. An additional field "**@type**" contains a URI identifying the type. Example: { "id": 1234, "@type": "types.example.com/standard/id" }.

done

boolean

If the value is **false**, it means the operation is still in progress. If **true**, the operation is completed, and either **error** or **response** is available.

Union field **result**. The operation result, which can be either an **error** or a valid **response**. If **done == false**, neither **error** nor **response** is set. If **done == true**, exactly one of **error** or **response** is set. **result** can be only one of the following:

error

object (Status

(<https://cloud.google.com/vision/automl/object-detection/docs/reference/rest/v1beta1/projects.locations.operations#Status>)
)

The error result of the operation in case of failure or cancellation.

Fields

response

object

The normal response of the operation in case of success. If the original method returns no data on success, such as **Delete**, the response is `google.protobuf.Empty`. If the original method is standard **Get/Create/Update**, the response should be the resource. For other methods, the response should have the type `XxxResponse`, where `Xxx` is the original method name. For example, if the original method name is `TakeSnapshot()`, the inferred response type is `TakeSnapshotResponse`.

An object containing fields of an arbitrary type. An additional field `@type` contains a URI identifying the type. Example: `{ "id": 1234, "@type": "types.example.com/standard/id" }`.

Status

The `Status` type defines a logical error model that is suitable for different programming environments, including REST APIs and RPC APIs. It is used by [gRPC](https://github.com/grpc) (<https://github.com/grpc>). Each `Status` message contains three pieces of data: error code, error message, and error details.

You can find out more about this error model and how to work with it in the [API Design Guide](https://cloud.google.com/apis/design/errors) (<https://cloud.google.com/apis/design/errors>).

JSON representation

```
{
  "code": number,
  "message": string,
  "details": [
    {
      "@type": string,
      field1: ...,
      ...
    }
  ]
}
```

Fields	
code	<p>number</p> <p>The status code, which should be an enum value of <code>google.rpc.Code</code>.</p>
message	<p>string</p> <p>A developer-facing error message, which should be in English. Any user-facing error message should be localized and sent in the <code>google.rpc.Status.details</code> (https://cloud.google.com/vision/automl/object-detection/docs/reference/rest/v1beta1/projects.locations.operations#Status.FIELDS.details) field, or localized by the client.</p>
details[]	<p>object</p> <p>A list of messages that carry the error details. There is a common set of message types for APIs to use.</p> <p>An object containing fields of an arbitrary type. An additional field "<code>@type</code>" contains a URI identifying the type. Example: <code>{ "id": 1234, "@type": "types.example.com/standard/id" }</code>.</p>

Methods	
<p><u>cancel</u></p> <p>(https://cloud.google.com/vision/automl/object-detection/docs/reference/rest/v1beta1/projects.locations.operations/cancel)</p>	<p>Starts asynchronous cancellation on a long-running operation.</p>
<p><u>delete</u></p> <p>(https://cloud.google.com/vision/automl/object-detection/docs/reference/rest/v1beta1/projects.locations.operations/delete)</p>	<p>Deletes a long-running operation.</p>
<p><u>get</u></p> <p>(https://cloud.google.com/vision/automl/object-detection/docs/reference/rest/v1beta1/projects.locations.operations/get)</p>	<p>Gets the latest state of a long-running operation.</p>

Methods

list

(<https://cloud.google.com/vision/automl/object-detection/docs/reference/rest/v1beta1/projects.locations.operations/list>)

Lists operations that match the specified filter in the request.

wait

(<https://cloud.google.com/vision/automl/object-detection/docs/reference/rest/v1beta1/projects.locations.operations/wait>)

Waits for the specified long-running operation until it is done or reaches at most a specified timeout, returning the latest state.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 4.0 License](https://creativecommons.org/licenses/by/4.0/) (<https://creativecommons.org/licenses/by/4.0/>), and code samples are licensed under the [Apache 2.0 License](https://www.apache.org/licenses/LICENSE-2.0) (<https://www.apache.org/licenses/LICENSE-2.0>). For details, see our [Site Policies](https://developers.google.com/terms/site-policies) (<https://developers.google.com/terms/site-policies>). Java is a registered trademark of Oracle and/or its affiliates.

Last updated August 29, 2019.