Cloud Vision API Product Search

AnnotatelmageRequest

Request for performing Google Cloud Vision API tasks over a user-provided image, with user-requested features, and with context information.

```
JSON representation
{
    "image": {
        object (Image (https://cloud.google.com/vision/product-search/docs/reference/rest/v1/AnnotateIm
    },
    "features": [
        {
            object (Feature (https://cloud.google.com/vision/product-search/docs/reference/rest/v1/Featur
      }
    ],
    "imageContext": {
        object (ImageContext (https://cloud.google.com/vision/product-search/docs/reference/rest/v1/Im
    }
}
```

Fields	
image	<pre>object (Image (https://cloud.google.com/vision/product- search/docs/reference/rest/v1/AnnotateImageRequest#Image)) The image to be processed.</pre>
features[]	object (Feature (https://cloud.google.com/vision/product- search/docs/reference/rest/v1/Feature)) Requested features.

Fields	
imageContext	object (ImageContext (https://cloud.google.com/vision/product- search/docs/reference/rest/v1/ImageContext)) Additional context that may accompany the image.

Image

Client image to perform Google Cloud Vision API tasks over.

```
JSON representation
{
    "content": string,
    "source": {
      object (<u>ImageSource</u> (https://cloud.google.com/vision/product-search/docs/reference/rest/v1/Ann
      }
}
```

}	
Fields	
content	string (bytes (https://developers.google.com/discovery/v1/type-format) format) Image content, represented as a stream of bytes. Note: As with all bytes fields, protobuffers use a pure binary representation, whereas JSON representations use base64. A base64-encoded string.
source	object (ImageSource (https://cloud.google.com/vision/product- search/docs/reference/rest/v1/AnnotateImageRequest#ImageSource)) Google Cloud Storage image location, or publicly-accessible image URL. If both content and source are provided for an image, content takes precedence and is used to perform the image annotation request.

ImageSource

External image source (Google Cloud Storage or web URL image location).

```
JSON representation
{
    "gcsImageUri": string,
    "imageUri": string
}
```

Fields gcsImageUri string Use imageUri instead. The Google Cloud Storage URI of the form gs://bucket_name/object_name. Object versioning is not supported. See Google Cloud Storage Request URIs (https://cloud.google.com/storage/docs/reference-uris) for more info. imageUri string The URI of the source image. Can be either: 1. A Google Cloud Storage URI of the form gs://bucket_name/object_name. Object versioning is not supported. See Google Cloud Storage Request URIs (https://cloud.google.com/storage/docs/reference-uris) for more info. 2. A publicly-accessible image HTTP/HTTPS URL. When fetching images

2. A publicly-accessible image HTTP/HTTPS URL. When fetching images from HTTP/HTTPS URLs, Google cannot guarantee that the request will be completed. Your request may fail if the specified host denies the request (e.g. due to request throttling or DOS prevention), or if Google throttles requests to the site for abuse prevention. You should not depend on externally-hosted images for production applications.

When both **gcsImageUri** and **imageUri** are specified, **imageUri** takes precedence.

Except as otherwise noted, the content of this page is licensed under the <u>Creative Commons Attribution 4.0 License</u> (https://creativecommons.org/licenses/by/4.0/), and code samples are licensed under the <u>Apache 2.0 License</u> (https://www.apache.org/licenses/LICENSE-2.0). For details, see our <u>Site Policies</u> (https://developers.google.com/terms/site-policies). Java is a registered trademark of Oracle and/or its affiliates.

Last updated June 6, 2019.